

Card
Printer



DC-8600

Next generation
Re-transfer printing



HIGHLIGHTS AT A GLANCE:

- High resolution printing with 600 dpi
- High productivity due to high speed printing
- Over-the-Edge full card printing
- High capacity card feeder
- Prepared for encoders



DASCOM[®]
SOLUTIONS FOR BUSINESS PRINTING

DC-8600

The DC-8600 is the next generation re-transfer printer from DASCUM. Available in two models the printer can hold up two different cards with a maximum capacity of 450 cards. With a print speed of up to 180 cards/hour and high capacity ribbons for 1.000 images the printer is not scared of large print jobs.

Both models have a USB and an Ethernet interface as standard and can be upgraded by a WiFi interface. The administration can be done via a browser through the DASCUM WebPanel.

TECHNICAL DATA

Print Method	Colour dye sublimation re-transfer technology
Resolution	600 dpi
Print Capability	Single Side, Double Side, Over-the-Edge, photo quality image colour
Print Speed	Single Side: 20 sec. Double Side: 45 sec.
Interfaces	USB (2.0), Ethernet (10/100) <i>Optional:</i> WiFi
Card Thickness	0,5 - 1,1 mm (20 - 50 mil)
Security Features	RFID ribbon, card feeder lock, custom watermarks (BMP)
Card Loading	<i>Standard:</i> Card feeder for 250 cards (0,76 mm thickness) <i>Double Bin:</i> Card feeder for 250 cards and 2nd card hopper for 200 cards Manual feed: single card
Card Types	PVC, PET, PET-G, PC 85,6 x 53,98 mm (ISO ID-1/CR-80 size)
Consumables	Ribbon YMCK (500 or 1.000 Images), Ribbon YMCKH (400 or 800 Images), Ribbon YMCKK (400 or 800 Images), Ribbon YMCKI (400 or 800 Images), Ribbon YMCKSI (350 or 700 Images), Transfer Film YMCK (500 or 1.000 Images) Ribbon K (500 or 1.000 Images), Transfer Film K (500 or 1.000 Images)
Cleaning Set	Cleaning Card Cleaning Roller
Physical Weight	<i>Standard:</i> 13,3 kg <i>Double Bin:</i> 15 kg
Physical Size	<i>Standard:</i> 248 x 339 x 408 mm (W x D x H) <i>Double Bin:</i> 248 x 466 x 408 mm (W x D x H)
Power Voltage	Auto wide ranging, 100 - 240 V AC - 50/60 Hz
Environment	Printing: +15° to +30° C Temperature; 35 - 95% Humidity Storage: +5° C to +45° C Temperature; 35 - 95% Humidity
Driver	Windows 8/8.1/10/11 and Server 2012/2016/2019/2022, macOS
Optional Encoder	Encoder prepared
Warranty	For more details please contact your local dealer



Standard model



Double bin model

CHINA
DASCUM (Holdings) LTD.
R. 1811-1816A | Nan Fung Center
264-298 Castle Peak Road | Tuen Wan, N. T.
Hong-Kong | P.R. CHINA
info.cn@dascom.com | www.dascom.com

APAC
DASCUM AP Pte. Ltd.
2 Jurong East Street 21 | # 05-42, IMM Building
Singapore 609601
sales@dascom.com.sg | www.dascom.com.sg

AMERICAS
DASCUM Americas.
34 Lakeview Court | Verona
Virginia, 24482 | USA
info.us@dascom.com | www.dascomamericas.com

EMEA
DASCUM Europe GmbH.
Heuweg 3
89079 Ulm | GERMANY
info.de@dascom.com | www.dascomeuope.de